

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number
WO 2004/006226 A1

- (51) International Patent Classification⁷: G10L 19/14, H04Q 7/30
- (21) International Application Number: PCT/CA2003/000980
- (22) International Filing Date: 27 June 2003 (27.06.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2,392,640 5 July 2002 (05.07.2002) CA
- (71) Applicant (for all designated States except US): VOICEAGE CORPORATION [CA/CA]; 750 chemin Lucerne, Suite 250, Ville Mont-Royal, Québec H3R 2H6 (CA).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): JELINEK, Milan [CA/CA]; 925 Walton, Sherbrooke, Quebec J1H 1K4 (CA). SALAMI, Redwan [CA/CA]; 4045 Place Albert-Dreux, Ville St-Laurent, Quebec H4R 2Y3 (CA).
- (74) Agents: BROUILLETTE, Robert et al.; Brouillette Kosie Prince, 1100, René-Lévesque Blvd. West, 25th Floor, Montréal, Québec, H3B 5C9 (CA).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR EFFICIENT IN-BAND DIM-AND-BURST SIGNALING AND HALF-RATE MAX OPERATION IN VARIABLE BIT-RATE WIDEBAND SPEECH CODING FOR CDMA WIRELESS SYSTEMS



(57) Abstract: In the method and device for interoperating a first station using a first communication scheme and comprising a first coder and a first decoder with a second station using a second communication scheme and comprising a second coder and a second decoder, communication between the first and second stations is conducted by transmitting signal-coding parameters related to a sound signal from the coder of one of the first and second stations to the decoder of the other station. The sound signal is classified to determine whether the signal-coding parameters should be transmitted from the coder of one station to the decoder of the other station using a first communication mode in which full bit rate is used for transmission of the signal-coding parameters. When classification of the sound signal determines that the signal-coding parameters should be transmitted using the first communication mode and when a request to transmit the signal-coding parameters from the coder of one station to the decoder of the other station using a second communication mode designed to reduce bit rate during transmission of the signal-coding parameters is received, a portion of the signal-coding parameters from the coder one station is dropped and the remaining signal-coding parameters are transmitting to the decoder of the other station using the second communication mode. The dropped portion of the signal-coding parameters are regenerated before the decoder of the other station decodes the signal-coding parameters.

BEST AVAILABLE COPY

WO 2004/006226 A1